



Description 50.583 Acres

in the Southeast Quarter of Section 11, Town 3 South, Range 3 East, York Township, Situated

Van Wert County, Ohio, being part of the west half of the southeast quarter as heretofore conveyed to Timothy D. Owens and Diana Kesler, by deed recorded in Official Record Volume 430, Page 683, of said County Deed Records and being more particularly

described as follows;

at the southwest corner of the southeast quarter said Section 11, being a monument box Beginning

along the westerly line of said southeast quarter, N.01°26'11"E., a distance of 1698.09 Thence

feet to a mag nail set;

running along a new division line, $S.87^{\circ}25'20"E.$, a distance of 1313.00 feet to a 5/8"Thence

iron pin set in the east line of said west half, passing a 5/8" iron pin set at 20.00 feet;

on the east line of said west half, $S.01^{\circ}18'13"W.$, a distance of 1653.95 feet to a 5/8" iron Thence

pin found at the southeast corner of the west half of the southeast quarter;

along the south line of said southeast quarter, N.89°20'46"W., a distance of 1316.70 feet Thence

to the Point of Beginning;

50.583 acres, more or less and being subject to all legal highways, rights-of-way, Containing

easements, restrictions, covenants, and/or conditions of record.

The above description based on a survey prepared by Michael L. Howbert, Registered Professional Surveyor No. 7959, in February of 2024. The basis of bearing is based on Ohio North State Plane Grid, NAD 83, Adjustment 2011.

Michael L. Howbert, P.S.





Description 18.782 Acres

Situated

in the Southeast Quarter of Section 11, Town 3 South, Range 3 East, York Township, Van Wert County, Ohio, being part of the west half of the southeast quarter as heretofore conveyed to Timothy D. Owens and Diana Kesler, by deed recorded in Official Record Volume 430, Page 683, of said County Deed Records and being more particularly described as follows;

Beginning

at the northwest corner of the southeast quarter said Section 11, being a monument box found:

Thence

along the north line of said southeast quarter, S.88°57'30"E., a distance of 1187.66 feet to a point in the centerline of the Little Auglaize River;

Thence

on a new division line on the following eight (8) courses and distances:

- 1. S.16°03'13"W., a distance of 176.23 feet to a point;
- 2. S.16°58'25"W., a distance of 254.36 feet to a point;
- 3. S.64°07'56"W., a distance of 153.78 feet to a point;
- 4. S.00°59'20"E., a distance of 331.15 feet to a 5/8" iron pin set;
- 5. N.88°11'25"W., a distance of 251.11 feet to a 5/8" iron set;
- 6. N.82°35'12"W., a distance of 358.80 feet to a 5/8" iron set;
- 7. N.78°11'12"W., a distance of 279.18 feet to a 5/8" iron set;
- 8. N.88°43'04"W., a distance of 69.82 feet to a mag nail set in the west line of said southeast quarter, passing a 5/8" iron pin set at 49.82 feet;

Thence

along the west line of said southeast quarter, N.01°26'11"E., a distance of 719.70 feet to the Point of Beginning;

Containing

18.782 acres, more or less and being subject to all legal highways, rights-of-way, easements, restrictions, covenants, and/or conditions of record.

The above description based on a survey prepared by Michael L. Howbert, Registered Professional Surveyor No. 7959, in February of 2024. The basis of bearing is based on Ohio North State Plane Grid, NAD 83, Adjustment 2011.

Michael L. Howbert, P.S.

